

TECHNICAL DATA SHEET

CALIBER® BLUE HS HEAVY DUTY GREASE

Whitmore's Caliber® Blue HS is primarily designed for use in heavy earthmoving and industrial equipment. The high protection from extreme pressure makes it suitable for use anywhere high load is encountered.

Protection from wear under high load is accomplished by the use of SL-Tech $^{\mathsf{TM}}$, a proprietary blend of light-colored solid lubricants. This forms a protective cushion and provides greater extreme pressure properties than MoS_2 or graphite. Protection is further enhanced by the use of selected additives that increase film strength and adhesive.

BENEFITS:

- VERSATILE FORMULATION one grease can cover all normal ambient temperature applications in the slow to medium speed range.
- EXTREME PRESSURE/ANTI-WEAR protects against scoring, high shock load conditions, thus reducing downtime and costs of replacement parts.
- SAFE contains no heavy metals or hazardous ingredients.

APPLICATIONS:

Caliber Blue HS grease is ideal for heavy-duty plant lubrication, earthmoving equipment and applications involving extreme pressure.

For the most severely loaded applications such as bearings on vertical roller mills, pelletizing mills or shaker screens, use Whitmore's Matrix® EP 2.

| ASTM# | | TYPICAL CHARACTERISTICS | | | |
|--------|------------------------------------|-------------------------|-----------|------------|------------|
| | NLGI Grade | 00 | 0 | 1 | 2 |
| D-2265 | Dropping Point, °F (°C) | | | 404 (207) | 404 (207) |
| D-445 | Kinematic Viscosity (with Polymer) | | | | |
| | cSt @ 40°C | 100.0 | 100.0 | 100.0 | 193.0 |
| | cSt @ 100°C | 12.0 | 12.0 | 12.0 | 13.0 |
| D-2596 | Four Ball EP | | | | |
| | Weld Point, kg | 400 | 500 | 500 | 500 |
| D-2266 | Four Ball Wear | | | | |
| | Scar Width, mm | 0.50 | 0.50 | 0.43 | 0.43 |
| D-1264 | Water Washout, % Loss | N/A | N/A | 5 - 8 | <5 |
| D-1743 | Rust Test | Pass | Pass | Pass | Pass |
| | Usable Temperature Range, | | | | |
| | °F | -30 to 30 | -25 to 60 | 0 to 230 | 10 to 230 |
| | °C | -34 to -1 | -32 to 16 | -18 to 110 | -12 to 110 |
| | Thickener Type | Lithium | Lithium | Lithium | Lithium |
| | Color | Blue | Blue | Blue | Blue |

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

| Drums | Kegs | Pails | Cartridges 50 Per Case |
|-------|------|-------|---------------------------|
|-------|------|-------|---------------------------|

For warranty information, scan the QR code.

whitmores.com

Made in the USA in an ISO 9001-2015 and ISO 14001:2015 Facility.

